



SAFETY JOGGER

INDUSTRIAL



Medium

ADVANCE S1 P

Leather Safety Shoe Steel Toe

Safety Jogger ADVANCE leather safety shoes combine sleek design a steel toecap, and slip resistance for reliable safety in demanding environments.

Upper	Carbon Action Leather
Lining	Recycled Mesh
Footbed	SJ foam footbed
Midsole	Steel
Outsole	PU/PU
Toecap	Steel
Category	S1 P / SR, FO
Size range	EU 36-47 / UK 3.5-12.0 / US 4.0-13.0 JPN 22.5-31 / KOR 235-310
Sample weight	0.667 kg
Norms	ASTM F2413:2018 EN ISO 20345:2022



T22




S1P

You work in dry environments, no risk of water/liquid sprays, and you need protection for your toes, protection against perforation, and a good breathability? Then you need S1P safety footwear.



SRC slip resistance

Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.



Oil & fuel resistant

The outsole is resistant against oil and fuel.



Steel toecap

Robust metal support to protect the feet of the wearer against falling or rolling objects.



Steel midsole

Puncture resistant steel midsoles are made from stainless or coated steel and prevent sharp objects from penetrating the outsole.



Heel energy absorption

Heel energy absorption reduces the impact of jumps or running on the body of the wearer.

**SAFETY
JOGGER**
WORKS

**HEAD-TO-TOE
PROTECTION**



Proudly ranked in the top 1% by EcoVadis for sustainability.

**ENGINEERED
IN EUROPE**

www.safetyjogger.com

Industries:

Automotive, Construction, Logistics, Industry

Environments:

Dry environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20345
Upper	Carbon Action Leather			
	Upper: permeability to water vapor	mg/cm ² /h	1.66	≥ 0.8
	Upper: water vapor coefficient	mg/cm ²	17	≥ 15
Lining	Recycled Mesh			
	Lining: permeability to water vapor	mg/cm ² /h	2.99	≥ 2
	Lining: water vapor coefficient	mg/cm ²	31	≥ 20
Footbed	SJ foam footbed			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	25600/12800	25600/12800
Outsole	PU/PU			
	Outsole abrasion resistance (volume loss)	mm ³	32	≤ 150
	Basic Slip resistance - Ceramic + NaLS - Forward heel slip	friction	0.43	≥ 0.31
	Basic Slip resistance - Ceramic + NaLS - Backward forepart slip	friction	0.41	≥ 0.36
	SR Slip resistance - Ceramic + glycerin - Forward heel slip	friction	0.31	≥ 0.19
	SR Slip resistance - Ceramic + glycerin - Backward forepart slip	friction	0.31	≥ 0.22
	Antistatic value	MegaOhm	36.7	0.1 - 1000
	ESD value	MegaOhm	N/A	0.1 - 100
	Heel energy absorption	J	26	≥ 20
Toecap	Steel			
	Impact resistance toecap (clearance after impact 100J)	mm	N/A	N/A
	Compression resistance toecap (clearance after compression 10kN)	mm	N/A	N/A
	Impact resistance toecap (clearance after impact 200J)	mm	15.5	≥ 14
	Compression resistance toecap (clearance after compression 15kN)	mm	19.0	≥ 14

Sample size:

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.



HEAD-TO-TOE
PROTECTION



Proudly ranked in the
top 1% by EcoVadis
for sustainability.



www.safetyjogger.com