



Medium

BESTBOY259 S3

All Bestboy2 features with wool lining & BASF PU/rubber outsole

The Safety Jogger BESTBOY259 safety shoes are perfect for high-risk industries. With features like SR slip resistance, a heat-resistant outsole, cold insulation, and water-resistant upper, they provide unparalleled safety. Enjoy less sweaty feet and body posture pain relief.


| | |
|---------------|---|
| Upper | Barton Action Leather |
| Lining | Fur |
| Footbed | Fur |
| Midsole | Steel |
| Outsole | PU/Rubber (NBR) |
| Toecap | Steel |
| Category | S3 / SR, SC, HI, CI, FO, HRO |
| Size range | EU 36-48 / UK 3.5-13.0 / US 4.0-13.5 JPN 22.5-31.5 / KOR 235-315 |
| Sample weight | 0.721 kg |
| Norms | ASTM F2413:2018 EN ISO 20345:2022 |



BLK




Warm lining
Keeps your feet warm and dry in cold environments.



S3
S3 safety shoes are suitable for work in an environment with high humidity and presence of oil or hydrocarbons. These shoes also protect against perforation risk of the sole, and foot crushing.




SRC slip resistance
Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.



Heat resistant outsole (HRO)
The outsole resists high temperatures up to 300°C.



Cold insulated (CI)
Cold insulated (CI) safety shoes keep your feet warm. They are worn in cold environments.



Water resistant Upper (WRU)
Prevents penetration of water if not permanently exposed to high levels.

Industries:

Chemical, Cleaning, Construction, Logistics, Mining, Oil & Gas

Environments:

Cold environment, Snowy and icy, Warm surfaces, Wet environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

| | Description | Measure unit | Result | EN ISO 20345 |
|----------------|--|-----------------------|-------------|--------------|
| Upper | Barton Action Leather | | | |
| | Upper: permeability to water vapor | mg/cm ² /h | 2.2 | ≥ 0.8 |
| | Upper: water vapor coefficient | mg/cm ² | 25.0 | ≥ 15 |
| Lining | Fur | | | |
| | Lining: permeability to water vapor | mg/cm ² /h | 7.7 | ≥ 2 |
| | Lining: water vapor coefficient | mg/cm ² | 65.6 | ≥ 20 |
| Footbed | Fur | | | |
| | Footbed: abrasion resistance (dry/wet) (cycles) | cycles | 25600/12800 | 25600/12800 |
| Outsole | PU/Rubber (NBR) | | | |
| | Outsole abrasion resistance (volume loss) | mm ³ | 100 | ≤ 150 |
| | Outsole slip resistance SRA: heel | friction | 0.38 | ≥ 0.28 |
| | Outsole slip resistance SRA: flat | friction | 0.40 | ≥ 0.32 |
| | Outsole slip resistance SRB: heel | friction | 0.14 | ≥ 0.13 |
| | Outsole slip resistance SRB: flat | friction | 0.18 | ≥ 0.18 |
| | Antistatic value | MegaOhm | 85.7 | 0.1 - 1000 |
| | ESD value | MegaOhm | N/A | 0.1 - 100 |
| | Heel energy absorption | J | 37 | ≥ 20 |
| Toecap | Steel | | | |
| | Impact resistance toecap (clearance after impact 100J) | mm | N/A | N/A |
| | Compression resistance toecap (clearance after compression 10kN) | mm | N/A | N/A |
| | Impact resistance toecap (clearance after impact 200J) | mm | 15.5 | ≥ 14 |
| | Compression resistance toecap (clearance after compression 15kN) | mm | 18.5 | ≥ 14 |

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.