

Medium

## BESTRUN231 S3

All-time, low-cut safety shoe

The Safety Jogger BESTRUN231 is an antistatic, oil and fuel-resistant safety shoe with a breathable leather upper and rubber outsole. It offers body posture pain relief, grip, and keeps feet dry and fresh.

|               |   |
|---------------|---|
| Upper         | Barton Action Leather   |
| Lining        | Mesh  |
| Footbed       | SJ foam footbed   |
| Midsole       | Steel   |
| Outsole       | BASF PU/BASF PU   |
| Toecap        | Steel   |
| Category      | S3 / SRC  |
| Size range    | EU 35-48 / UK 3.0-13.0 / US 3.0-13.5<br>JPN 21.5-31.5 / KOR 230-315 |
| Sample weight | 0.640 kg  |
| Norms         | ASTM F2413:2018<br>EN ISO 20345:2011                                |




BLK



### Breathable leather upper

Natural leather provides a high degree of wearer comfort combined with durability in versatile applications.



### Oil & fuel resistant

The outsole is resistant against oil and fuel.



### Steel midsole

Puncture resistant steel midsoles are made from stainless or coated steel and prevent sharp objects from penetrating the outsole.



### Self-cleaning outsole

Self-cleaning outsoles are designed to reduce clogging of the profile.



### Steel toecap

Robust metal support to protect the feet of the wearer against falling or rolling objects.



### SRC slip resistance

Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.

**Industries:**

Automotive, Catering, Chemical, Cleaning, Construction, Food &amp; beverages, Logistics, Oil &amp; Gas, Industry

**Environments:**

Muddy environment, Dry environment

**Maintenance instructions:**

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

|                | Description  | Measure unit          | Result      | EN ISO 20345 |
|----------------|--|-----------------------|-------------|--------------|
| <b>Upper</b>   | <b>Barton Action Leather</b>                                     |                       |             |              |
|                | Upper: permeability to water vapor                               | mg/cm <sup>2</sup> /h | 2.2         | ≥ 0.8        |
|                | Upper: water vapor coefficient                                   | mg/cm <sup>2</sup>    | 25          | ≥ 15         |
| <b>Lining</b>  | <b>Mesh</b>  |                       |             |              |
|                | Lining: permeability to water vapor                              | mg/cm <sup>2</sup> /h | 49.8        | ≥ 2          |
|                | Lining: water vapor coefficient                                  | mg/cm <sup>2</sup>    | 398.8       | ≥ 20         |
| <b>Footbed</b> | <b>SJ foam footbed</b>   |                       |             |              |
|                | Footbed: abrasion resistance (dry/wet) (cycles)                  | cycles                | 25600/12800 | 25600/12800  |
| <b>Outsole</b> | <b>BASF PU/BASF PU</b>   |                       |             |              |
|                | Outsole abrasion resistance (volume loss)                        | mm <sup>3</sup>       | 56.4        | ≤ 150        |
|                | Outsole slip resistance SRA: heel                                | friction              | 0.37        | ≥ 0.28       |
|                | Outsole slip resistance SRA: flat                                | friction              | 0.34        | ≥ 0.32       |
|                | Outsole slip resistance SRB: heel                                | friction              | 0.14        | ≥ 0.13       |
|                | Outsole slip resistance SRB: flat                                | friction              | 0.18        | ≥ 0.18       |
|                | Antistatic value   | MegaOhm               | 120.7       | 0.1 - 1000   |
|                | ESD value  | MegaOhm               | N/A         | 0.1 - 100    |
|                | Heel energy absorption   | J                     | 29          | ≥ 20         |
| <b>Toecap</b>  | <b>Steel</b>   |                       |             |              |
|                | Impact resistance toecap (clearance after impact 100J)           | mm                    | N/A         | N/A          |
|                | Compression resistance toecap (clearance after compression 10kN) | mm                    | N/A         | N/A          |
|                | Impact resistance toecap (clearance after impact 200J)           | mm                    | 15          | ≥ 14         |
|                | Compression resistance toecap (clearance after compression 15kN) | mm                    | 15          | ≥ 14         |

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.