



Medium

COOL 02

Low comfortable full-leather sneaker

Sporty and slip-resistant ESD occupational sneaker made from natural Nappa leather

Upper	Leather
Lining	Mesh
Footbed	SJ foam footbed
Outsole	Rubber (NBR)
Category	O2 / ESD, SRC, FO, HRO
Size range	EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 JPN 21.5-31.5 / KOR 230-315
Sample weight	0.436 kg
Norms	ASTM F2892:2018 EN ISO 20347:2012



BLK



WHT



Oxygrip / SJ Grip
Rubber outsoles with Oxytraction® technology provide excellent traction on both dry and wet floors and meet SRC (SRA+ SRB) standards.

Breathable leather upper
Natural leather provides a high degree of wearer comfort combined with durability in versatile applications.

Electrostatic Discharge (ESD)
ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 100 MegaOhm.

SRC slip resistance
Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.

Heel energy absorption
Heel energy absorption reduces the impact of jumps or running on the body of the wearer.

Forefoot energy absorption
Forefoot energy absorption reduces the impact of jumps or running on the body of the wearer.

Industries:

Catering, Cleaning, Food & beverages, Medical, Industry, Uniform

Environments:

Dry environment, Extreme slippery surfaces

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20347
Upper	Leather			
	Upper: permeability to water vapor	mg/cm ² /h	1.38	≥ 0.8
	Upper: water vapor coefficient	mg/cm ²	17	≥ 15
Lining	Mesh			
	Lining: permeability to water vapor	mg/cm ² /h	37.3	≥ 2
	Lining: water vapor coefficient	mg/cm ²	299	≥ 20
Footbed	SJ foam footbed			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	25600/12800	25600/12800
Outsole	Rubber (NBR)			
	Outsole abrasion resistance (volume loss)	mm ³	130	≤ 150
	Outsole slip resistance SRA: heel	friction	0.36	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.37	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.18	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.25	≥ 0.18
	Antistatic value	MegaOhm	171.4	0.1 - 1000
	ESD value	MegaOhm	32	0.1 - 100
	Heel energy absorption	J	24	≥ 20

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.