



Medium

## DUNE OB

### High-cut all round desert boot

The robust DUNE safety boots provide SR slip resistance, antistatic properties, breathable comfort, and are equipped with a zipper. They offer body posture pain relief, multiple usages, and hot surface resistance.

Upper	Suede Leather, Textile
Lining	Mesh
Footbed	SJ foam footbed
Outsole	Rubber (NBR)
Category	OB / E, HI, CI, FO, HRO
Size range	EU 38-48 / UK 5.0-13.0 / US 5.5-13.5 JPN 24-31.5 / KOR 250-315
Sample weight	0.710 kg
Norms	EN ISO 20347:2022+A1:2024



SND



#### Antistatic

Antistatic footwear prevents build-up of static electrical charges and ensures that they are discharged effectively. Volume resistance between 100 KiloOhm and 1 GigaOhm



#### Breathable upper

Increased moisture and temperature management for extended wearer comfort.



#### SRC slip resistance

Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.

**Industries:**

Tactical

**Environments:**

Dry environment, Uneven surfaces

**Maintenance instructions:**

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20347
<b>Upper</b>	<b>Suede Leather, Textile</b>			
	Upper: permeability to water vapor	mg/cm <sup>2</sup> /h	4.5	≥ 0.8
	Upper: water vapor coefficient	mg/cm <sup>2</sup>	35	≥ 15
<b>Lining</b>	<b>Mesh</b>			
	Lining: permeability to water vapor	mg/cm <sup>2</sup> /h	45	≥ 2
	Lining: water vapor coefficient	mg/cm <sup>2</sup>	350	≥ 20
<b>Footbed</b>	<b>SJ foam footbed</b>			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	25600/12800	25600/12800
<b>Outsole</b>	<b>Rubber (NBR)</b>			
	Outsole abrasion resistance (volume loss)	mm <sup>3</sup>	85	≤ 150
	Basic Slip resistance - Ceramic + NaLS - Forward heel slip	friction	0.33	≥ 0.31
	Basic Slip resistance - Ceramic + NaLS - Backward forepart slip	friction	0.37	≥ 0.36
	SR Slip resistance - Ceramic + glycerin - Forward heel slip	friction	N/A	≥ 0.19
	SR Slip resistance - Ceramic + glycerin - Backward forepart slip	friction	N/A	≥ 0.22
	Antistatic value	MegaOhm	N/A	0.1 - 1000
ESD value	MegaOhm	N/A	0.1 - 100	
	Heel energy absorption	J	N/A	≥ 20

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.