

ECO PRODRY 2131X

ECOPRODRY

Performance level	2131X
Liner	15 GAUGE POLYESTER
Coating	LATEX/LATEX SANDY
Size range	EU 7-12
Sample weight	0.048 kg
Norms	ANSI/ISEA 105:2016 EN ISO 21420:2020 EN 388:2016









EN 388:2016





Industries:

Assembly, Automotive, Chemical, Cleaning, Construction, Industry, Logistics, Mining, Oil & Gas, Tactical



Performance level 2131X

EN388:2016	0	1	2	3	4	5
a. Abrasion resistance (cycles)	<100	100	500	2000	8000	-
b. Cut resistance (factor)	< 1.2	1.2	2.5	5.0	10.0	20.0
c. Tear resistance (newton)	< 10	10	25	50	75	-
d. Puncture resistance (newton)	< 20	20	60	100	150	-

EN ISO 13997 (TDM-100 test)	Α	В	C	D	E	F
e. Straight blade cut resistance (newton)	2	5	10	15	22	30

- a. Abrasion resistance: based on the number of cycles required to rub through the sample glove.
- b. Cut resistance: based on the number of cycles required to cut through the sample at a constant speed with a rotating blade.
- c. Tear resistance: based on the amount of force required to tear the sample.
- d. Puncture resistance: based on the amount of force required to pierce the sample with a standard sized point.
- e. Cut resistance according TDM100 test based on the number of cycles required to cut through the sample at a constant speed with a sliding blade.







Water repellent

Keeps your hands dry by repelling water and moisture.

Extraordinary grip

You'll have a firm hold on objects whether they are dry, wet, or oily, thanks to the exceptional grip these gloves provide.

Double layer coating

These gloves have two layers of coating: the first layer offers superior protection, while the second provides excellent grip, even in wet or humid conditions.

High dexterity

These gloves are made from the thinnest knit material available, ensuring the highest level of dexterity, comfort and protection.

