



## ECO PROTECTOR 4X44C

ECOPROTECT

Performance level	4X44C
Liner	13 GAUGE HPPE
Coating	NITRILE/NITRILE SANDY
Size range	EU 7-12
Sample weight	0.056 kg
Norms	ANSI/ISEA 105:2016 EN 407:2020 EN ISO 21420:2020 EN 388:2016



EN ISO 21420

EN 388:2016



### Industries:

Automotive, Chemical, Cleaning, Logistics, Mining, Oil & Gas, Tactical, Industry, Construction, Assembly



GBL

### Performance level 4X44C

EN388:2016	0	1	2	3	4	5
<b>a. Abrasion resistance (cycles)</b>	< 100	100	500	2000	8000	-
<b>b. Cut resistance (factor)</b>	< 1.2	1.2	2.5	5.0	10.0	20.0
<b>c. Tear resistance (newton)</b>	< 10	10	25	50	75	-
<b>d. Puncture resistance (newton)</b>	< 20	20	60	100	150	-

EN ISO 13997 (TDM-100 test)	A	B	C	D	E	F
<b>e. Straight blade cut resistance (newton)</b>	2	5	10	15	22	30

- Abrasion resistance: based on the number of cycles required to rub through the sample glove.
- Cut resistance: based on the number of cycles required to cut through the sample at a constant speed with a rotating blade.
- Tear resistance: based on the amount of force required to tear the sample.
- Puncture resistance: based on the amount of force required to pierce the sample with a standard sized point.
- Cut resistance according TDM100 test based on the number of cycles required to cut through the sample at a constant speed with a sliding blade.

**Water repellent**

Keeps your hands dry by repelling water and moisture.

**High cut resistance**

These gloves provide high protection against cuts, shielding your hands from sharp edges or objects. They are suitable for tasks that involve a moderate risk of cuts.

**All-round protection**

These gloves offer great all-round protection, keeping your hands safe in many different environments.

**Oil resistant**

The gloves can handle oils, greases, and solvents without breaking down. They are ideal for jobs involving mechanical work, or professions in the manufacturing, maintenance or the oil industry.

**High abrasion resistance**

These gloves are built to withstand heavy use without wearing out quickly. They meet the highest level of abrasion resistance according to the EN 388 standard.

**Latex free**

These gloves have extra padding to protect your palms and knuckles from impacts, reducing the risk of injury.