



Medium

ELA 01

Sporty and trendy sneaker for her

The shock-absorbent ELA sneaker seamlessly combines comfort and safety with ESD-technology, a removable footbed, memory foam insole, body posture pain relief and superior grip making it perfect for various environments.

| | |
|---------------|--|
| Upper | Synthetic Leather |
| Lining | Mesh |
| Footbed | SJ foam footbed |
| Outsole | PU/Rubber (NBR) |
| Category | O1 / ESD, SRC |
| Size range | EU 35-42 / UK 3.0-8.0 / US 5.5-10.5 JPN 21.5-26.5 / KOR 230-270 |
| Sample weight | 0.328 kg |
| Norms | ASTM F2892:2018 EN ISO 20347:2012 |



FUX



Memory foam

The removable memory foam insole provides extra comfort during stepping and can be exchanged with your own orthopedic sole.



Electrostatic Discharge (ESD)

ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 100 MegaOhm.



Removable insole

Renew your insole at a regular base or use your own orthopedic insoles for a higher comfort.

Industries:

Catering, Cleaning, Food & beverages, Medical

Environments:

Dry environment, Extreme slippery surfaces

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

| | Description | Measure unit | Result | EN ISO 20347 |
|----------------|---|-----------------------|-------------|--------------|
| Upper | Synthetic Leather | | | |
| | Upper: permeability to water vapor | mg/cm ² /h | 1.1 | ≥ 0.8 |
| | Upper: water vapor coefficient | mg/cm ² | 17.0 | ≥ 15 |
| Lining | Mesh | | | |
| | Lining: permeability to water vapor | mg/cm ² /h | 33.3 | ≥ 2 |
| | Lining: water vapor coefficient | mg/cm ² | 266.5 | ≥ 20 |
| Footbed | SJ foam footbed | | | |
| | Footbed: abrasion resistance (dry/wet) (cycles) | cycles | 25600/12800 | 25600/12800 |
| Outsole | PU/Rubber (NBR) | | | |
| | Outsole abrasion resistance (volume loss) | mm ³ | 124 | ≤ 150 |
| | Outsole slip resistance SRA: heel | friction | 0.48 | ≥ 0.28 |
| | Outsole slip resistance SRA: flat | friction | 0.57 | ≥ 0.32 |
| | Outsole slip resistance SRB: heel | friction | 0.15 | ≥ 0.13 |
| | Outsole slip resistance SRB: flat | friction | 0.19 | ≥ 0.18 |
| | Antistatic value | MegaOhm | 0.32 | 0.1 - 1000 |
| | ESD value | MegaOhm | 74 | 0.1 - 100 |
| | Heel energy absorption | J | 38 | ≥ 20 |

Sample size: 38

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.