



# SAFETY JOGGER

PROFESSIONAL



Light

## JAMES OB

**Sporty and ultra-light sneaker for him**

The JAMES sporty and ultra-light sneakers offer unmatched comfort with a removable footbed, 3D mesh, and superior support.

|               |                                                                   |
|---------------|-------------------------------------------------------------------|
| Upper         | Mesh                                                              |
| Lining        | Mesh                                                              |
| Footbed       | SJ foam footbed                                                   |
| Outsole       | Phylon/Rubber (NBR)                                               |
| Category      | OB / SRA, E                                                       |
| Size range    | EU 36-47 / UK 3.5-12.0 / US 4.0-13.0<br>JPN 22.5-31 / KOR 235-310 |
| Sample weight | 0.330 kg                                                          |
| Norms         | ASTM F2892:2024<br>EN ISO 20347:2012                              |



LGR



BLK



NAV



**3D mesh**  
Three-dimensional produced distance mesh to provide increased moisture and temperature management.



**Coolmax® lining**  
Coolmax® technology was originally developed for athletes. The material transports moisture and sweat, so that the body stays dry. We found it extremely suitable for people who work hard for hours every day too.



**Removable insole**  
Renew your insole at a regular base or use your own orthopedic insoles for a higher comfort.



**Solutions for every workplace**

INDUSTRIAL   PROFESSIONAL   TACTICAL   TIGER GRIP

ENGINEERED  
IN EUROPE

www.safetyjogger.com

**Industries:**

Catering, Food &amp; beverages, Medical

**Environments:**

Dry environment

**Maintenance instructions:**

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

|                | Description                                     | Measure unit          | Result      | EN ISO 20347 |
|----------------|-------------------------------------------------|-----------------------|-------------|--------------|
| <b>Upper</b>   | <b>Mesh</b>                                     |                       |             |              |
|                | Upper: permeability to water vapor              | mg/cm <sup>2</sup> /h | 1.4         | ≥ 0.8        |
|                | Upper: water vapor coefficient                  | mg/cm <sup>2</sup>    | 15.5        | ≥ 15         |
| <b>Lining</b>  | <b>Mesh</b>                                     |                       |             |              |
|                | Lining: permeability to water vapor             | mg/cm <sup>2</sup> /h | 28.9        | ≥ 2          |
|                | Lining: water vapor coefficient                 | mg/cm <sup>2</sup>    | 231.3       | ≥ 20         |
| <b>Footbed</b> | <b>SJ foam footbed</b>                          |                       |             |              |
|                | Footbed: abrasion resistance (dry/wet) (cycles) | cycles                | 25600/12800 | 25600/12800  |
| <b>Outsole</b> | <b>Phylon/Rubber (NBR)</b>                      |                       |             |              |
|                | Outsole abrasion resistance (volume loss)       | mm <sup>3</sup>       | 81          | ≤ 150        |
|                | Outsole slip resistance SRA: heel               | friction              | 0.48        | ≥ 0.28       |
|                | Outsole slip resistance SRA: flat               | friction              | 0.45        | ≥ 0.32       |
|                | Outsole slip resistance SRB: heel               | friction              | N/A         | ≥ 0.13       |
|                | Outsole slip resistance SRB: flat               | friction              | N/A         | ≥ 0.18       |
|                | Antistatic value                                | MegaOhm               | N/A         | 0.1 - 1000   |
|                | ESD value                                       | MegaOhm               | N/A         | 0.1 - 100    |
|                | Heel energy absorption                          | J                     | 34          | ≥ 20         |

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.