

JUMADI OB

JUMADIOB

Comfortable, lightweight and ultra breathable occupational trainer with wider toebox

Safety Jogger's JUMADI OB is a lightweight, ultra-breathable occupational shoe that features superior slip resistance and a removable footbed. Ideal for dry environments in assembly, logistics, medical, or catering industries.

Upper	Mesh
Lining	Mesh
Footbed	SJ foam footbed
Outsole	EVA/Rubber (NBR)
Category	OB / SR, E
Size range	EU 35-48
Sample weight	0.297 kg
Norms	EN ISO 20347:2022+A1:2024

























Breathable upper

Increased moisture and temperature management for extended wearer comfort.



Slip resistance (SR)

Replaces the previously used term of SRA+SRB=SRC. SR means the slip test has been executed on tiles contaminated with soap and with oil.



Industries:

Catering, Medical, Assembly, Logistics

Environments:

Dry environment

	Description	Measure unit	Result	EN ISO 20347
Upper	Mesh			
	Upper: permeability to water vapor	mg/cm²/h	30.55	≥ 0.8
	Upper: water vapor coefficient	mg/cm²	244	≥ 15
Lining	Mesh			
	Lining: permeability to water vapor	mg/cm²/h	30.55	≥ 2
	Lining: water vapor coefficient	mg/cm²	244	≥ 20
Footbed	SJ foam footbed			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	Dry 25600 cycles/Wet 12800 cycles	25600/12800
Outsole	EVA/Rubber (NBR)			
	Outsole abrasion resistance (volume loss)	mm³	60	≤ 150
	Basic Slip resistance - Ceramic + NaLS - Forward heel slip	friction	0.44	≥ 0.31
	Basic Slip resistance - Ceramic + NaLS - Backward forepart slip	friction	0.38	≥ 0.36
	SR Slip resistance - Ceramic + glycerin - Forward heel slip	friction	0.24	≥ 0.19
	SR Slip resistance - Ceramic + glycerin - Backward forepart slip	friction	0.24	≥ 0.22
	Antistatic value	MegaOhm	N/A	0.1 - 1000
	ESD value	MegaOhm	N/A	0.1 - 100
	Heel energy absorption	J	34	≥ 20

Sample size: 38

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.



