

# SAFETY JOGGER

PROFESSIONAL



Light

## LAUREN

### Light and airy shoe with an adjustable strap

The LAUREN clogs offer exceptional comfort and moisture management. Equipped with an adjustable strap, vegan-friendly and suitable for various industries, these shoes combine performance and affordability.

|               |  |
|---------------|--|
| Upper         | Mesh, Synthetic  |
| Lining        | Mesh   |
| Footbed       | Oxy Basic  |
| Outsole       | EVA  |
| Size range    | EU 35-42 / UK 3.0-8.0 / US 5.5-10.5<br>JPN 21.5-26.5 / KOR 230-270 |
| Sample weight | 0.140 kg   |



BLK



WHT



#### Breathable upper

Increased moisture and temperature management for extended wearer comfort.



#### Coolmax® lining

Coolmax® technology was originally developed for athletes. The material transports moisture and sweat, so that the body stays dry. We found it extremely suitable for people who work hard for hours every day too.



#### Vegan

Uses or contains no animal products.

**Industries:**

Catering, Cleaning, Food &amp; beverages, Medical

**Environments:**

Dry environment

**Maintenance instructions:**

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

|                | Description  | Measure unit          | Result      |             |
|----------------|--|-----------------------|-------------|-------------|
| <b>Upper</b>   | <b>Mesh, Synthetic</b>   |                       |             |             |
|                | Upper: permeability to water vapor                               | mg/cm <sup>2</sup> /h | N/A         | ≥ 0.8       |
|                | Upper: water vapor coefficient                                   | mg/cm <sup>2</sup>    | N/A         | ≥ 15        |
| <b>Lining</b>  | <b>Mesh</b>  |                       |             |             |
|                | Lining: permeability to water vapor                              | mg/cm <sup>2</sup> /h | N/A         | ≥ 2         |
|                | Lining: water vapor coefficient                                  | mg/cm <sup>2</sup>    | N/A         | ≥ 20        |
| <b>Footbed</b> | <b>Oxy Basic</b>   |                       |             |             |
|                | Footbed: abrasion resistance (dry/wet) (cycles)                  | cycles                | 25600/12800 | 25600/12800 |
| <b>Outsole</b> | <b>EVA</b>   |                       |             |             |
|                | Outsole abrasion resistance (volume loss)                        | mm <sup>3</sup>       | N/A         | ≤ 150       |
|                | Basic Slip resistance - Ceramic + NaLS - Forward heel slip       | friction              | N/A         | ≥ 0.31      |
|                | Basic Slip resistance - Ceramic + NaLS - Backward forepart slip  | friction              | N/A         | ≥ 0.36      |
|                | SR Slip resistance - Ceramic + glycerin - Forward heel slip      | friction              | N/A         | ≥ 0.19      |
|                | SR Slip resistance - Ceramic + glycerin - Backward forepart slip | friction              | N/A         | ≥ 0.22      |
|                | Antistatic value   | MegaOhm               | N/A         | 0.1 - 1000  |
|                | ESD value  | MegaOhm               | N/A         | 0.1 - 100   |
|                | Heel energy absorption   | J                     | N/A         | ≥ 20        |

Sample size: 38

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.