

SAFETY JOGGER

PROFESSIONAL

Heavy

OXYCLOG OB

The clog that meets all your needs

The OXYCLOG clogs are versatile, durable, and comfortable clogs with exceptional slip resistance, ESD, and is washable, autoclavable, and UV sterilizable.

Upper	TPE
Lining	N/A
Footbed	SJ foam footbed
Outsole	TPE
Category	OB / ESD, A, SRA, E
Size range	EU 35-48 / UK 3.0- / US 5.5- JPN 21.5- / KOR 230-
Sample weight	0.248 kg
Norms	ASTM F2892:2018 EN ISO 20347:2012



BLU



BLK



EBL



EGN



FUX



LBL



RED



WHT



Autoclavable
Can be sterilized in an autoclave.



Electrostatic Discharge (ESD)
ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 100 MegaOhm.



SRA slip resistance
Slip resistance is one of the most important features of safety and occupational footwear. SRA slip resistant soles are tested on a ceramic tile with dilute soap solution.



Washable 90°C
These shoes can be washed in a washing machine at 90°C.



Chemically & UV sterilizeable
This shoe is chemically and UV sterilizeable.



Hygienic waterproof solution
This shoe is made with materials that are waterproof, antibacterial and extremely light & flexible. This makes it a safe, hygienic and comfortable solution for applications in wet environments, such as cleaning or escorting patients into the shower.

Industries:

Medical, Food & beverages, Cleaning

Environments:

Dry environment, Extreme slippery surfaces, Uneven surfaces, Wet environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20347
Upper	TPE			
	Upper: permeability to water vapor	mg/cm ² /h	N/A	≥ 0.8
	Upper: water vapor coefficient	mg/cm ²	N/A	≥ 15
Lining	N/A			
	Lining: permeability to water vapor	mg/cm ² /h	N/A	≥ 2
	Lining: water vapor coefficient	mg/cm ²	N/A	≥ 20
Footbed	SJ foam footbed			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	25600/12800	25600/12800
Outsole	TPE			
	Outsole abrasion resistance (volume loss)	mm ³	120	≤ 150
	Outsole slip resistance SRA: heel	friction	0.41	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.41	≥ 0.32
	Outsole slip resistance SRB: heel	friction	N/A	≥ 0.13
	Outsole slip resistance SRB: flat	friction	N/A	≥ 0.18
	Antistatic value	MegaOhm	90	0.1 - 1000
	ESD value	MegaOhm	N/A	0.1 - 100
	Heel energy absorption	J	34	≥ 20

Sample size: 38

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.