



Light

SAMANTHA OB

Comfortabele veterloze schoen voor vrouwen

Our elevated comfy SAMANTHA clogs offer SR slip resistance, electrostatic discharge protection, and a breathable upper for ultimate comfort and safety. Designed for various industries and suitable for dry and extreme slippery surfaces.

| | |
|---------------|--|
| Upper | Lorica |
| Lining | Mesh |
| Footbed | SJ foam footbed |
| Outsole | Phylon/Rubber (NBR) |
| Category | OB / ESD, A, SRC, E |
| Size range | EU 35-42 / UK 3.0-8.0 / US 5.5-10.5 JPN 21.5-26.5 / KOR 230-270 |
| Sample weight | 0.260 kg |
| Norms | ASTM F2892:2018 EN ISO 20347:2012 |



FUC



BLK



LBL




LGN



LLC



WHT



Oxygrip / SJ Grip

Rubber outsoles with Oxytraction® technology provide excellent traction on both dry and wet floors and meet SRC (SRA+ SRB) standards.



Electrostatic Discharge (ESD)

ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 100 MegaOhm.




Breathable upper

Increased moisture and temperature management for extended wearer comfort.



SRC slip resistance

Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.



Removable insole

Renew your insole at a regular base or use your own orthopedic insoles for a higher comfort.

Industries:

Catering, Cleaning, Food & beverages, Medical

Environments:

Dry environment, Extreme slippery surfaces

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

| | Description | Measure unit | Result | EN ISO 20347 |
|----------------|---|-----------------------|-------------|--------------|
| Upper | Lorica | | | |
| | Upper: permeability to water vapor | mg/cm ² /h | 9.4 | ≥ 0.8 |
| | Upper: water vapor coefficient | mg/cm ² | 78 | ≥ 15 |
| Lining | Mesh | | | |
| | Lining: permeability to water vapor | mg/cm ² /h | 43.7 | ≥ 2 |
| | Lining: water vapor coefficient | mg/cm ² | 350 | ≥ 20 |
| Footbed | SJ foam footbed | | | |
| | Footbed: abrasion resistance (dry/wet) (cycles) | cycles | 25600/12800 | 25600/12800 |
| Outsole | Phylon/Rubber (NBR) | | | |
| | Outsole abrasion resistance (volume loss) | mm ³ | 81.9 | ≤ 150 |
| | Outsole slip resistance SRA: heel | friction | 0.47 | ≥ 0.28 |
| | Outsole slip resistance SRA: flat | friction | 0.41 | ≥ 0.32 |
| | Outsole slip resistance SRB: heel | friction | 0.21 | ≥ 0.13 |
| | Outsole slip resistance SRB: flat | friction | 0.23 | ≥ 0.18 |
| | Antistatic value | MegaOhm | N/A | 0.1 - 1000 |
| | ESD value | MegaOhm | 70 | 0.1 - 100 |
| | Heel energy absorption | J | 38.9 | ≥ 20 |

Sample size: 38

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.