



Light

# SUNNY OB

**Sporty and fashionable sneaker for her**

The SUNNY sneakers offer dry comfort with superior support for body posture pain relief and excellent grip. Perfect for demanding industries.

|               |  |
|---------------|--|
| Upper         | Synthetic Leather  |
| Lining        | Mesh   |
| Footbed       | SJ foam footbed  |
| Outsole       | TPR  |
| Category      | OB / E   |
| Size range    | EU 35-42 / UK 3.0-8.0 / US 5.5-10.5<br>JPN 21.5-26.5 / KOR 230-270 |
| Sample weight | 0.347 kg   |
| Norms         | EN ISO 20347:2022(Europe)  |



LBL



FUX

LGR

LIC



**Coolmax® lining**  
Coolmax® technology was originally developed for athletes. The material transports moisture and sweat, so that the body stays dry. We found it extremely suitable for people who work hard for hours every day too.

**Industries:**

Catering, Cleaning, Food &amp; beverages, Medical

**Environments:**

Dry environment

**Maintenance instructions:**

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

|                | Description  | Measure unit          | Result      | EN ISO 20347 |
|----------------|--|-----------------------|-------------|--------------|
| <b>Upper</b>   | <b>Synthetic Leather</b>   |                       |             |              |
|                | Upper: permeability to water vapor                               | mg/cm <sup>2</sup> /h | 1.1         | ≥ 0.8        |
|                | Upper: water vapor coefficient                                   | mg/cm <sup>2</sup>    | 16.8        | ≥ 15         |
| <b>Lining</b>  | <b>Mesh</b>  |                       |             |              |
|                | Lining: permeability to water vapor                              | mg/cm <sup>2</sup> /h | 51.4        | ≥ 2          |
|                | Lining: water vapor coefficient                                  | mg/cm <sup>2</sup>    | 412.1       | ≥ 20         |
| <b>Footbed</b> | <b>SJ foam footbed</b>   |                       |             |              |
|                | Footbed: abrasion resistance (dry/wet) (cycles)                  | cycles                | 25600/12800 | 25600/12800  |
| <b>Outsole</b> | <b>TPR</b>   |                       |             |              |
|                | Outsole abrasion resistance (volume loss)                        | mm <sup>3</sup>       | 135         | ≤ 150        |
|                | Basic Slip resistance - Ceramic + NaLS - Forward heel slip       | friction              | 0.33        | ≥ 0.31       |
|                | Basic Slip resistance - Ceramic + NaLS - Backward forepart slip  | friction              | 0.38        | ≥ 0.36       |
|                | SR Slip resistance - Ceramic + glycerin - Forward heel slip      | friction              | N/A         | ≥ 0.19       |
|                | SR Slip resistance - Ceramic + glycerin - Backward forepart slip | friction              | N/A         | ≥ 0.22       |
|                | Antistatic value   | MegaOhm               | N/A         | 0.1 - 1000   |
|                | ESD value  | MegaOhm               | N/A         | 0.1 - 100    |
|                | Heel energy absorption   | J                     | 23.0        | ≥ 20         |

Sample size: 38

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.